

## Notes

## Stravifloor Jackup-R (EN)

- The structural floor should comply with the required tolerances regarding gradient (0,1% or 1 mm/m) and smoothness (max. 2 mm). It should be dry and free of obstacles, discontinuities, dust, etc.
  - A rigid connection should be avoided between the floating slab and all vertical elements (as walls, columns, ...) by adding a void or a layer of lateral isolation between the isolated slab and the vertical element.
- For more detailed information ask for Stravifloor Jackup-R Installation Manual.

MINIMUM SYSTEM TOTAL BUILD-UP HEIGHT (BEFORE DEFLECTION): 110mm

## Legend

Second submission	29/07/2025	PGR	B
First submission	23/07/2025	VPR	A
Revision Description	Date Drawn Rev.		

## Load table

## Drawing based on




Reutenebeek 9-11  
B-3090 Overijse Belgium  
PH: +32 2 687 97 07  
FX: +32 2 687 35 52  
info@cdm-stravitec.com  
www.cdm-stravitec.com

## STRAVIFLOOR JACKUP-R WITH ELASTOMERIC BEARING

 $\$(GETVAR,-\$(GETVAR,??))$ 

Scale: 1 : 5  
Drawn: \_\_\_\_\_  
PGR 29/07/2025  
Design: \_\_\_\_\_  
CRU  
Check: \_\_\_\_\_  
CRU

Format: A3  
A3



## Notes

## Stravifloor Jackup-R (EN)

- The structural floor should comply with the required tolerances regarding gradient (0,1 % or 1 mm/m) and smoothness (max. 2 mm). It should be dry and free of obstacles, discontinuities, dust, etc.
  - A rigid connection should be avoided between the floating slab and all vertical elements (as walls, columns, ...) by adding a void or a layer of lateral isolation between the isolated slab and the vertical element.
- For more detailed information ask for Stravifloor Jackup-R Installation Manual.

MINIMUM SYSTEM TOTAL BUILD-UP HEIGHT (BEFORE DEFLECTION): 110mm  
+ INSULATION MATERIAL THICKNESS

## Legend

Second submission	29/07/2025	PGR	B
First submission	23/07/2025	VPR	A
Revision Description			
Date	Drawn	Rev.	

## Load table

Drawing based on

---

---

---

**cdm**  
**stravitec**

Reutenebeek 9-11  
B-3090 Overijse Belgium  
PH: +32 2 687 79 07  
FX: +32 2 687 35 52  
info@cdm-stravitec.com  
www.cdm-stravitec.com


This drawing is exclusive property of CDM Stravitec, any reproduction or communication to third parties without prior authorisation is prohibited.  
**STRAVIFLOOR JACKUP-R WITH ELASTOMERIC BEARINGS, FRAME OVERHEIGHT AND INSULATION MATERIAL**

$\$(GETVAR,-\$(GETVAR,??))$

Scale:  
1 : 5

Drawn: \_\_\_\_\_  
PGR 29/07/2025  
Design: \_\_\_\_\_  
CRU  
Check: \_\_\_\_\_  
CRU

Format:  
A3



## Notes

Stravifloor Jackup-R (EN)

- The structural floor should comply with the required tolerances regarding gradient (0,1% or 1 mm/m) and smoothness (max. 2 mm). It should be dry and free of obstacles, discontinuities, dust, etc.
  - A rigid connection should be avoided between the floating slab and all vertical elements (as walls, columns, ...) by adding a void or a layer of lateral isolation between the isolated slab and the vertical element.
- For more detailed information ask for Stravifloor Jackup-R Installation Manual.

MINIMUM SYSTEM TOTAL BUILD-UP HEIGHT (BEFORE DEFLECTION): 105mm

## Legend

Second submission	29/07/2025	PGR	B
First submission	23/07/2025	VPR	A
Revision Description	Date Drawn Rev.		

## Load table

Drawing based on



Reutenebeek 9-11  
B-3090 Overijse Belgium  
PH: +32 2 687 79 07  
FX: +32 2 687 35 52  
info@cdm-stravitec.com  
www.cdm-stravitec.com


## STRAVIFLOOR JACKUP-R WITH SPRING BEARING

 $\$(GETVAR,- \$(GETVAR,??))$ 

Scale:  
1 : 5

Drawn: \_\_\_\_\_  
PGR 29/07/2025  
Design: \_\_\_\_\_  
CRU  
Check: \_\_\_\_\_  
CRU

Format:  
A3

## Notes

## Stravifloor Jackup-R (EN)

- The structural floor should comply with the required tolerances regarding gradient (0,1 % or 1 mm/m) and smoothness (max. 2 mm). It should be dry and free of obstacles, discontinuities, dust, etc.
  - A rigid connection should be avoided between the floating slab and all vertical elements (as walls, columns, ...) by adding a void or a layer of lateral isolation between the isolated slab and the vertical element.
- For more detailed information ask for Stravifloor Jackup-R Installation Manual.

MINIMUM SYSTEM TOTAL BUILD-UP HEIGHT (BEFORE DEFLECTION): 105mm  
+ INSULATION MATERIAL THICKNESS

## Legend

Second submission	29/07/2025	PGR	B
First submission	23/07/2025	VPR	A
Revision Description	Date Drawn Rev.		

## Load table

## Drawing based on

**cdm**  
**stravitec**


Reutenebeek 9-11  
B-3090 Overijse Belgium  
PH: +32 2 687 97 07  
FX: +32 2 687 35 52  
info@cdm-stravitec.com  
www.cdm-stravitec.com


STRAVIFLOOR JACKUP-R WITH SPRING BEARINGS,  
FRAME OVERHEIGHT AND INSULATION MATERIAL

$\$(GETVAR,-\$(GETVAR,??))$

Scale:  
1 : 5  
Drawn:  
PGR 29/07/2025  
Design:  
CRU  
Check:  
CRU

Format:  
A3  
A3





**Notes**

System **Stravifloor Jackup-R (EN)**

1. The structural floor should comply with the required tolerances regarding gradient (0,1 % or 1 mm/m) and smoothness (max. 2 mm).  
It should be dry and free of obstacles, discontinuities, dust, etc.

2. A rigid connection should be avoided between the floating slab and all vertical elements (as walls, columns, ...) by adding a void or a layer of lateral isolation between the isolated slab and the vertical element.

For more detailed information ask for **Stravifloor Jackup-R Installation Manual**.

MINIMUM SYSTEM TOTAL BUILD-UP HEIGHT (BEFORE DEFLECTION): 105mm  
+ INSULATION MATERIAL THICKNESS

Legend

Second submission	29/07/2025	PGR	B
First submission	23/07/2025	VPR	A
Revision Description	Date	Drawn	Rev.

Load table

---

Drawing based on

---

---

---



Reutenebeek 9-11  
B-3090 Overijse Belgium  
PH: +32 2 687 79 07  
FX: +32 2 687 35 52  
info@cdm-stravitec.com  
www.cdm-stravitec.com

This drawing is exclusive property of CDM Stravitec, any reproduction or communication to third parties without prior authorisation is prohibited.

**STRAVIFLOOR JACKUP-R TYPICAL TOP VIEW**

$\$(GETVAR,- \$(GETVAR,??))$

Scale:  
1 : 5

Drawn: \_\_\_\_\_  
PGR 29/07/2025  
Design: \_\_\_\_\_  
CRU  
Check: \_\_\_\_\_  
CRU

Format:  
A3