

Stravigym Gym- pactFloor-P14.5 Datasheet

Stravigym GympactFloor-P14.5 is a compact and robust [rubber flooring product](#) with high compression resistance, high friction (non-slip), is resistant to wear and tear. The material is a composition of a 2.5 mm (1/16") Vulcanized Composition Rubber (VCR) Surface Layer combined with a 12 mm (1/2") up-cycled VCR.

Stravigym GympactFloor can be used as stand-alone finish flooring or as finishing of Stravigym solutions (Stravigym SP, HP and XP, or Stravigym GympactLayer).

It is available as an interlocking puzzle (P).



SYSTEM DIMENSIONS

Interlocking Puzzle Tiles

Length x Width - 0.58 mm (23") x 0.58 mm (23")


Thickness - 14.5 mm (9/16"), being a combination of glued 2.5 mm (1/16") surface layer with a 12 mm (1/2") base layer




AVAILABLE COLORS*




Black




Red/Grey




Grey




Blue/Grey



Blue



Red



Light Grey



Brown

* Other colors available upon request. Product images are for illustrative purposes only and may differ from the actual product.



PHYSICAL & MECHANICAL PROPERTIES

	Test Standard	Typical Results
Recovery after Static Load	ASTM F970	0.23 mm (0,009")
Coefficient of Friction	ASTM D2047	>0.8
FloorScore	CA 01350	Certified
Abrasion Resistance	ASTM D3389	Pass
Flammability-Pill Test	ASTM D2859	Pass

DISCLAIMER

This information is accurate to the best of our knowledge at the time of issue. Information, data and recommendations provided are based on industry accepted testing and prior product usage. It is intended as descriptive of the general capabilities and performance of our products and does not endorse applicability for any particular project. We reserve the right to change products, performance, and data without notice. This document replaces all information supplied prior to the publication hereof.