



Stravifloor Mat-W15_x* Datasheet

Stravifloor Mat-W15 $_{\rm x}$ is a mat made of upcycled polyurethane foam and cellular rubber for rolling noise isolation of floating slabs and screeds.



SYSTEM COMPONENTS & DIMENSIONS

- Mat dimension: 1.25 m x 5 m x 15/7 mm
- Pallet information: 11 rolls/pallet pallet: 1200x800x1400 mm 400 kg



PHYSICAL & MECHANICAL PROPERTIES

Mechanical properties

Max. total load 0.1 MPa	Max. occasional load 1 MPa	Density ⁽¹⁾ 400 kg/m ³	Surface weight ⁽¹⁾ 4.4 kg/m ²
Tensile strength ⁽²⁾ > 0.25 MPa	Elongation at break ⁽²⁾ > 50 %	Creep rate ⁽³⁾ 0.76 % H/dec	Cdyn ⁽⁴⁾ 9 MN/m ³


(1)|SO 845 - (2)|SO 37 - (3)|SO 8013, at 0.02 mPa - (4)|EN 29052-1


Thermal Properties

Temperature range	Reaction to fire	Thermal conductivity	Thermal resistance
-30°C / 80°C	Class E ⁽¹⁾ / Class B2 ⁽²⁾	0.10 W/m°C ⁽³⁾	0.150 m2°C/W ⁽³⁾

(1)EN 13501-1 - (2)DIN 4102 - (3)EN 12667

*Previously known as CDM-MTX-15/7






фр


ACOUSTICAL RESULTS

Test Report Itecons ACL281-17* - Test Setup

- 1. Standard reinforced concrete floor (140 mm)
- 2. Stravifloor Mat-W15_x
- 3. Floating floor: reinforced concrete slab (70 mm)

*Laboratory report available upon request







DISCLAIMER

This information is accurate to the best of our knowledge at the time of issue. Information, data and recommendations provided are based on industry accepted testing and prior product usage. It is intended as descriptive of the general capabilities and performance of our products and does not endorse applicability for any particular project. We reserve the right to change products, performance, and data without notice. This document replaces all information supplied prior to the publication hereof.